

Thuyết minh thông số kỹ thuật mô tả Cisco Catalyst 1200 Series Switches C1200-24P-4X datasheet

C1200-24P-4X	24x 10/100/1000 PoE+ ports with 195W power budget 4x 10 Gigabit SFP+ 10G Rack-mountable
CPU	Dual-core ARM at 1.4 GHz
Flash	512 MB
DRAM	1 GB DDR4
Packet buffer	1.5 MB
Performance Capacity	95.23 (mpps)
Performance Switching capacity	128.0 (Gbps)
Unit weight	3.68 kg (8.11 lb)
Unit dimensions (W x D x H)	445 x 299 x 44 mm (17.5 x 11.77 x 1.73 in)
Console port	Cisco standard RJ-45 console port and USB Type C port
USB port	USB Type C port on the front panel of the switch for easy file and image management as well as console port
Buttons	Reset button
Cabling type	Unshielded Twisted Pair (UTP) Category 5e or better for 1000BASE-T
LEDs	System, Link/Act, PoE, Speed
Power	100 to 240V 50 to 60 Hz, internal, universal: C1200-16T-2G, C1200-16P-2G, C1200-24T-4G, C1200-24P-4G, C1200-24FP-4G, C1200-48T-4G, C1200-48P-4G, C1200-24T-4X, C1200-24P-4X, C1200-24FP-4X, C1200-48T-4X, C1200-48P-4X
	100 to 240V 50 to 60 Hz, external: C1200-8T-D, C1200-8T-E-2G, C1200-8P-E-2G, C1200-8FP-E-2G
Certifications	UL (UL 62368), CSA (CSA 22.2), CE mark, FCC Part 15 (CFR 47) Class A
Operating temperature	32° to 122°F (0° to 50°C) for C1200-8T-D
	23° to 122°F (-5° to 50°C) for other models
Storage temperature	-13° to 158°F (-25° to 70°C)
Operating humidity	10% to 90%, relative, noncondensing
Storage humidity	10% to 90%, relative, noncondensing
Package contents	Cisco Catalyst 1200 Series Switch
	Power cord (power adapter for select 8-port and 16-port SKUs)
	Mounting kit
	Pointer card