

Thuyết minh thông số kỹ thuật mô tả Cisco Catalyst 1300 Series Switches C1300-24FP-4X-EU datasheet

| | |
|--------------------------------|---|
| C1300-24FP-4X | 24x 10/100/1000 PoE+ ports with 375W power budget 4x 10 Gigabit SFP+ Rack-mountable |
| CPU | ARM dual-core at 1.4 GHz |
| Flash | 512 MB |
| DRAM | 1 GB DDR4 |
| Packet buffer | 1.5 MB |
| Performance Capacity | 95.23 (mpps) |
| Performance Switching capacity | 128.0 (Gbps) |
| Unit weight | 4.6 kg (10.14 lb) |
| Unit dimensions (W x D x H) | 445 x 345 x 44 mm (17.5 x 13.59 x 1.73 in) |
| Console port | Cisco standard RJ-45 console port and USB Type C port |
| USB port | USB Type C port on the front panel of the switch for easy file and image management as well as console port |
| Buttons | Reset button |
| Cabling type | Unshielded Twisted Pair (UTP) Category 5e or better for 1000BASE-T |
| LEDs | System, Link/Act, PoE, Speed |
| Power | 100-240V 50-60 Hz, internal, universal: C1300-8FP-2G, C1300-16T-2G, C1300-16P-2G, C1300-16FP-2G, C1300-24T-4G, C1300-24P-4G, C1300-24FP-4G, C1300-48T-4G, C1300-48P-4G, C1300-48FP-4G, C1300-16P-4X, C1300-24T-4X, C1300-24P-4X, C1300-24FP-4X, C1300-48T-4X, C1300-48P-4X. |
| | 100-240V 50-60 Hz, external: C1300-8T-E-2G, C1300-8P-E-2G |
| Certifications | UL (UL 62368), CSA (CSA 22.2), CE mark, FCC Part 15 (CFR 47) Class A |
| Operating temperature | 23° to 122°F (-5° to 50°C) |
| | C1300-8T-E-2G, C1300-8P-E-2G, C1300-8FP-2G, C1300-16T-2G, C1300-16P-2G, C1300-16FP-2G, C1300-24T-4G, C1300-24P-4G, C1300-24FP-4G, C1300-48T-4G, C1300-48P-4G, C1300-48FP-4G, C1300-16P-4X, C1300-24T-4X, C1300-24P-4X, C1300-24FP-4X, C1300-48T-4X, C1300-48P-4X |
| | 32° to 122°F (0° to 50°C) |
| Storage temperature | -13° to 158°F (-25° to 70°C) |
| Operating humidity | 10% to 90%, relative, noncondensing |
| Storage humidity | 10% to 90%, relative, noncondensing |
| Package contents | Cisco Catalyst 1300 Series Switch |
| | Power cord (power adapter for select 8-port and 16-port SKUs) |
| | Mounting kit |
| | Pointer card |
| Warranty | Limited lifetime with next-business-day advance replacement (where available) |