

Thuyết minh thông số kỹ thuật mô tả Cisco Catalyst 1300 Series Switches C1300-8P-E-2G-EU datasheet

C1300-8P-E-2G	8x 10/100/1000 PoE+ ports with 60W power budget 2x Gigabit copper/SFP combo ports Rack-mountable
CPU	ARM dual-core at 1.4 GHz
Flash	512 MB
DRAM	1 GB DDR4
Packet buffer	1.5 MB
Performance Capacity	14.88 (mpps)
Performance Switching capacity	20.0 (Gbps)
Unit weight	1.53 kg (3.37 lb)
Unit dimensions (W x D x H)	268 x 185 x 44 mm (10.56 x 7.28 x 1.73 in)
Console port	Cisco standard RJ-45 console port and USB Type C port
USB port	USB Type C port on the front panel of the switch for easy file and image management as well as console port
Buttons	Reset button
Cabling type	Unshielded Twisted Pair (UTP) Category 5e or better for 1000BASE-T
LEDs	System, Link/Act, PoE, Speed
Power	100-240V 50-60 Hz, internal, universal: C1300-8FP-2G, C1300-16T-2G, C1300-16P-2G, C1300-16FP-2G, C1300-24T-4G, C1300-24P-4G, C1300-24FP-4G, C1300-48T-4G, C1300-48P-4G, C1300-48FP-4G, C1300-16P-4X, C1300-24T-4X, C1300-24P-4X, C1300-24FP-4X, C1300-48T-4X, C1300-48P-4X. 100-240V 50-60 Hz, external: C1300-8T-E-2G, C1300-8P-E-2G
Certifications	UL (UL 62368), CSA (CSA 22.2), CE mark, FCC Part 15 (CFR 47) Class A
Operating temperature	23° to 122°F (-5° to 50°C) C1300-8T-E-2G, C1300-8P-E-2G, C1300-8FP-2G, C1300-16T-2G, C1300-16P-2G, C1300-16FP-2G, C1300-24T-4G, C1300-24P-4G, C1300-24FP-4G, C1300-48T-4G, C1300-48P-4G, C1300-48FP-4G, C1300-16P-4X, C1300-24T-4X, C1300-24P-4X, C1300-24FP-4X, C1300-48T-4X, C1300-48P-4X 32° to 122°F (0° to 50°C)
Storage temperature	-13° to 158°F (-25° to 70°C)
Operating humidity	10% to 90%, relative, noncondensing
Storage humidity	10% to 90%, relative, noncondensing
Package contents	Cisco Catalyst 1300 Series Switch Power cord (power adapter for select 8-port and 16-port SKUs) Mounting kit Pointer card
Warranty	Limited lifetime with next-business-day advance replacement (where available)