

Thuyết minh thông số kỹ thuật sản phẩm

Switch Cisco Catalyst C9300L-24P-4G-E



C9300L-24P-4G-E Catalyst 9300 24-port 1G copper, with fixed 4x1G SFP uplinks, PoE+ Network Essentials

Performance & Bandwidth thông số	
Mã part	C9300L-24P-4G-E
Cấu hình	24-port 1G copper PoE+
	fixed 4x1G SFP uplinks
Total number of MAC addresses	32,000
Total number of IPv4 routes	32,000 (24,000 direct routes and 8000 indirect routes)
IPv6 routing entries	16,000
Multicast routing scale	8,000
QoS scale entries	5,120
ACL scale entries	5,120
Packet buffer per SKU	16 MB buffer for 24 and 48 port Gigabit Ethernet models
FNF entries	64,000 flow on 24- and 48-port Gigabit Ethernet models
DRAM	8 GB
Flash	16 GB
VLAN IDs	4094
Total Switched Virtual Interfaces (SVIs)	1000
Jumbo frames	9198 bytes
Total routed ports per C9300 Series stack	416
Switching capacity	56 Gbps
Switching capacity with stacking	376 Gbps
Forwarding rate	41.66 Mpps
Forwarding rate with stacking	279.76 Mpps
Stacking support	StackWise-320
Stacking bandwidth support	320 Gbps
Optional Stacking hardware	C9300L-STACK-KIT
Number of members	8
Supported stack members	Other C9300L SKUs with same license level
Thông số kỹ thuật nguồn	
Nguồn cho Cisco 9300L	PWR-C1-715WAC-P; PWR-C1-715WAC-P/2
Power supply rated maximum output power	715W
Total output BTU	2440 BTU/hr, 715W
(note: 1000 BTU/hr = 293W)	
Input-voltage range and frequency	100 to 240 VAC,
	50 to 60 Hz
Input current	10-5A
Output ratings	-56V at 12.8A
Output holdup time	20 ms minimum at 100VAC
Power-supply input receptacles	IEC 320-C16
	(IEC60320-C16)
Power cord rating	15A
Physical specifications	(H x W x D): 1.58 x 3.25 x 12.20 in

Physical specifications	Weight: 2.6 lb (1.2 kg)
Operating temperature	Normal operating temperature* and altitudes:
	• -5°C to +45°C, up to 5000 feet (1500m)
	• -5°C to +40°C, up to 10,000 feet (3000m)
	Minimum ambient temperature for cold start is 32°F (0°C)
	Short-term* exceptional conditions:
	• -5°C to +50°C, up to 5000 feet (1500m)
	• -5°C to +45°C, up to 10,000 feet (3000m)
	• -5°C to +45°C, at sea level with single fan failure
	*Not more than following in one-year period: 96 consecutive hours, or 360 hours total, or 15 occurrences
Storage temperature	-40° to 158°F (-40° to 70°C)
Relative humidity operating and nonoperating noncondensing	5% to 90% noncondensing
Altitude	10,000 ft. (3000 meters), up to 45°C
EMI and EMC compliance	FCC Part 15 (CFR 47) Class A
	ICES-003 Class A
	EN 55032 Class A
	CISPR 32 Class A
	AS/NZS 3548 Class A
	BSMI Class A (AC input models only)
	VCCI Class A
	EN 55024, EN300386, EN 61000-3-2, EN 61000-3-3
	EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6, EN 61000-6-1
LED indicators	"AC OK": Input power to the power supply is OK
	"PS OK": Output power from the power supply is OK
DNA mua kèm Switch Cisco Catalyst 9300L	
Network Essentials	Tính năng Network Essentials
✓	Switch fundamentals
	Layer 2, Routed Access (RIP, EIGRP Stub, OSPF - 1000 routes), PBR, PIM Stub Multicast (1000 routes)), PVLAN, VRRP, PBR, CDP, QoS, FHS, 802.1X, MACsec-128, CoPP, SXP, IP SLA Responder, SSO
✗	Advanced switch capabilities and scale
	BGP, EIGRP, HSRP, IS-IS, BSR, MSDP, PIM-BIDIR,* IP SLA, OSPF
✗	Network segmentation
	VRF, VXLAN, LISP, SGT, MPLS, mVPN
✓	Automation
	NETCONF, RESTCONF, gRPC, YANG, PnP Agent, ZTP/Open PnP, GuestShell (On-Box Python)
✓	Telemetry and visibility
	Model-driven telemetry, sampled NetFlow, SPAN, RSPAN
✗	High availability and resiliency
	Nonstop Forwarding (NSF), Graceful Insertion and Removal (GIR), Fast Software Upgrade (FSU), Software Patching (CLI Based)
✗	IOT integration
	AVB, PTP, CoAP
✗	Security
	MACsec-256
Cisco DNA Essentials	Tính năng Cisco DNA Essentials
	Switch features
	Optimized network deployments
✗	Cisco DNA Service for Bonjour
	Advanced telemetry and visibility
✓	Full Flexible NetFlow, EEM
	Optimized telemetry and visibility
✗	ERSPAN, AVC (NBAR2), app hosting (in containers/VMs), Wireshark
	Advanced security
✗	

✓	Encrypted Traffic Analytics (ETA)
	Cisco DNA Center features
✓	Day-0 network bring-up automation
	Cisco Network Plug-and-Play application, network settings, device credentials, LAN automation, host onboarding
✓	Element management
	Discovery, inventory, topology, software image, licensing, and configuration management
X	Element management
	Patch management
✓	Basic Assurance
	Health dashboards – Network, Client, Application; switch and wired client health monitoring
X	SD-Access
	Policy-based automation and assurance for wired and wireless
X	SD-Access Embedded Wireless
	C9800 Wireless Software package to enable Wireless Controller Functionality
X	Network assurance and analytics
	Global insights, trends, compliance, custom reports; switch 360, wired client 360; fabric and non-fabric insights; app health, app 360, app performance (loss, latency, jitter)
	Other Software included (can be purchased separately)
X	ISE Base
X	ISE Plus
X	StealthWatch