## Thuyết minh thông số kỹ thuật Switch Cisco CBS250-24P-4X-EU

Mô tả	Cisco CBS250-24P-4X-EU L2-Managed Gigabit POE Switch 24 Port Gigabit, 4 Port SFP+ 10Gbps, POE 195W ,VLAN, Spanning Tree Protocol (STP), Access Control List (ACL), Quality Of Service (QoS), IPv4/IPv6 static routing
Capacity in millions of packets per second (mpps) (64-byte packets)	95.23 mpps
Switching capacity in gigabits per second (Gbps)	128.0 Gbps
Power over Ethernet (PoE)	
802.3at PoE+ and 802.3af PoE delivered ove any of the RJ-45 ports within the listed power budgets	The following switches support 802.3at PoE+, 802.3af, and Cisco prestandard (legacy) PoE. Maximum power of 30.0W to any 10/100 or Gigabit Ethernet port, until the PoE budget for the switch is reached. The total power available for PoE per switch is as follows:
Power dedicated to PoE	195W
Number of ports that support PoE	24
Port	
RJ-45 ports	24
SFP, SFP+	4 Port SFP+
Console port	Cisco Standard mini USB Type-B / RJ45 console port
USB slot	USB Type-A slot on the front panel of the switch for easy file and image management
Buttons	Reset button
Cabling type	Unshielded Twisted Pair (UTP) Category 5e or better for 1000BASE-T
LEDs	System, Link/Act, PoE, Speed
Flash	256 MB
CPU	800 MHz ARM
DRAM	512 MB
Packet buffer	1.5MB
Unit dimensions (W x H x D)	445 x 299 x 44 mm (17.5 x 11.76 x 1.73 in)
Unit weight	3.68 kg (8.11 lb)
Power	100 to 240V 50 to 60 Hz, internal, universal: CBS250-16T-2G, CBS250-16P-2G, CBS250-24T-4G, CBS250-24P-4G, CBS250-24F-4G, CBS250-48F-4G, CBS250-48P-4G, CBS250-48P-4G, CBS250-24T-4X, CBS250-24P-4X, CBS250-24F-4X, CBS250-24F-4X, CBS250-48F-4X100 to 240V 50 to 60 Hz, external: CBS250-8T-E-2G, CBS250-8PP-E-2G, CBS250-8P-E-2G, CBS250-8FP-E-2G
Certification	UL (UL 60950), CSA (CSA 22.2), CE mark, FCC Part 15 (CFR 47) Class A
Operating temperature	23° to 122°F (-5° to 50°C)
Storage temperature	-13° to 158°F (-25° to 70°C)
Operating humidity	10% to 90%, relative, noncondensing
Package contents	Cisco Business 250 Series Smart Switch
	Power cord (power adapter for 8-port SKUs)
	Mounting kit
	Quick Start Guide