

Thuyết minh thông số kỹ thuật Switch Cisco CBS250-24T-4G-EU

Mô tả	Cisco CBS250-24T-4G-EU L2-Managed Gigabit Switch 24 Port Gigabit, 4 Port SFP ,VLAN, Spanning Tree Protocol (STP), Access Control List (ACL), Quality Of Service (QoS), IPv4/IPv6 static routing
Capacity in millions of packets per second (mpps) (64-byte packets)	41.66 mpps
Switching capacity in gigabits per second (Gbps)	56 Gbps
Port	
RJ-45 ports	24
Combo ports (RJ-45 + SFP)	4
Console port	Cisco Standard mini USB Type-B / RJ45 console port
USB slot	USB Type-A slot on the front panel of the switch for easy file and image management
Buttons	Reset button
Cabling type	Unshielded Twisted Pair (UTP) Category 5e or better for 1000BASE-T
LEDs	System, Link/Act, PoE, Speed
Flash	256 MB
CPU	800 MHz ARM
DRAM	512 MB
Packet buffer	1.5MB
Unit dimensions (W x H x D)	445 x 240 x 44 mm (17.5 x 9.45 x 1.73 in)
Unit weight	2.63 kg (5.80 lb)
Power	100 to 240V 50 to 60 Hz, internal, universal: CBS250-16T-2G, CBS250-16P-2G, CBS250-24T-4G, CBS250-24PP-4G, CBS250-24P-4G, CBS250-24FP-4G, CBS250-48T-4G, CBS250-48PP-4G, CBS250-
Certification	UL (UL 60950), CSA (CSA 22.2), CE mark, FCC Part 15 (CFR 47) Class A
Operating temperature	23° to 122°F (-5° to 50°C)
Storage temperature	-13° to 158°F (-25° to 70°C)
Operating humidity	10% to 90%, relative, noncondensing
Package contents	Cisco Business 250 Series Smart Switch
	Power cord (power adapter for 8-port SKUs)
	Mounting kit
	Quick Start Guide