

Thuyết minh thông số kỹ thuật Switch L3 Cisco CBS350-48T-4X-EU

| | |
|---|---|
| Mô tả | Cisco CBS350-48T-4X-EU L3-Managed Gigabit Switch 48 Port Gigabit, 4 Port SFP+ 10Gbps,VLAN, Spanning Tree Protocol (STP), Advanced Threat Protection, IPv6 first-hop security, Quality Of Service (QoS), sFlow, IPv4/IPv6 static routing |
| Capacity in millions of packets per second (mpps) (64-byte packets) | 130.94 mpps |
| Switching capacity in gigabits per second (Gbps) | 176 Gbps |
| Ports | |
| RJ-45 Ports | 48 |
| Small form-factor pluggable [SFP+] (10Gbps) | 4 |
| Console port | Cisco Standard mini USB Type-B / RJ45 console port |
| USB slot | USB Type-A slot on the front panel of the switch for easy file and image management |
| Buttons | Reset button |
| Cabling type | Unshielded Twisted Pair (UTP) Category 5e or better for 1000BASE-T |
| LEDs | System, Link/Act, PoE, Speed |
| Flash | 256 MB |
| CPU | 800 MHz ARM |
| DRAM | 512 MB |
| Packet buffer | 3 MB |
| Unit dimensions (W x H x D) | 445 x 273 x 44 mm (17.5 x 10.73 x 1.73 in) |
| Unit Weight | 3.95 kg (8.71 lb) |
| Certification | UL (UL 60950), CSA (CSA 22.2), CE mark, FCC Part 15 (CFR 47) Class A |
| Operating temperature | 23° to 122°F (-5° to 50°C) |
| Storage temperature | -13° to 158°F (-25° to 70°C) |
| Operating humidity | 10% to 90%, relative, noncondensing |
| Storage humidity | 10% to 90%, relative, noncondensing |
| Package Contents | Cisco Business 350 Series Managed Switch |
| | Power Cord (Power adapter for select 8-port and 16-port SKUs) |
| | Mounting Kit |
| | Quick Start Guide |