## Thuyết minh thông số kỹ thuật Switch mạng Cisco CBS350-8FP-E-2G-EU

Cisco CBS350-8FP-E-2G-EU L3-Managed Gigabit POE Switch 8 Port Gigabit, 2 Port SFP Combo, POE 120W External Power Supply, VLAN, Spanning Tree Protocol (STP), Advanced Threat Protection, IPv6 first-hop security, Quality Of Service (QoS), sFlow, IPv4/IPv6 static routing
14.88 mpps
20 Gbps
Frame sizes up to 9K bytes. The default MTU is 2K bytes
16K addresses
The switch advertises itself using the Bonjour protocol
LLDP allows the switch to advertise its identification, configuration, and capabilities to neighboring devices that store the data in a MIB. LLDP-MED is an enhancement to LLDP that adds the extensions needed for
802.3at PoE+ and 802.3af PoE delivered over any of the RJ-45 ports within the listed power budgets
120W
8
8
2
Cisco Standard mini USB Type-B / RJ45 console port
USB Type-A slot on the front panel of the switch for easy file and image management
Reset button
Unshielded Twisted Pair (UTP) Category 5e or better for 1000BASE-T
System, Link/Act, PoE, Speed
256 MB
800 MHz ARM
512 MB
1.5 MB
268 x 185 x 44 mm (10.56 x 7.28 x 1.73 in)
3.5 kg (7.72 lb)
UL (UL 60950), CSA (CSA 22.2), CE mark, FCC Part 15 (CFR 47) Class A
23° to 122°F (-5° to 50°C)
-13° to 158°F (-25° to 70°C)
10% to 90%, relative, noncondensing
10% to 90%, relative, noncondensing
Cisco Business 350 Series Managed Switch
Power Cord (Power adapter for select 8-port and 16-port SKUs) Mounting Kit